

MATERIAL SAFETY DATA SHEET

CR-520 INSIDE FLOOR FINISH

SECTION I

Product Identification and General Information

Product Name: CR-520 INSIDE FLOOR FINISH

HMIS Codes: Health: 1
Flammability: 1
Reactivity: 0

Date Prepared: 4/24/2007
24 Hour Emergency Assistance
Chemtrec: 1-800-424-9300
MSDS Code - J895

SECTION II

Hazardous Ingredients

	<u>CAS#</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Glycol Ether DPM	34590-94-8	100 ppm	100 ppm
*Glycol Ether DE	111-90-0	N/A	N/A
Acrylate Polymer	67366-74-9	N/A	N/A
Ethylene Polymer	67892-91-5	N/A	N/A

***THIS CHEMICAL IS SUBJECT TO THE REPORTING REQUIREMENTS FOR SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372.**

SECTION III

Physical Data

Boiling Point: 190°-212° F
Vapor Pressure: Not Established
pH (conc.): 8.5
Specific Gravity: 1.030
Percent Volatiles: > 80%

Solubility in Water: Soluble
Evaporation Rate: < water
Appearance: White liquid
Odor: Mild Ammonia

SECTION IV

Fire and Explosion Hazard Data

Flash Point (Method Used) – None
Flammable Limits – Not determined
LEL – N/A
UEL – N/A

Extinguishing Media – Use water spray, dry chemical, carbon dioxide or foam extinguishing agents unless contraindicated by surrounding environment.

Special Fire Fighting Procedures – Prevent human exposure to fire, smoke, fumes or products of combustion. Evacuate non-essential personnel from fire area.

Fire fighters should wear appropriate protective equipment, including self contained breathing apparatus and impervious clothing. Keep containers cooled with water spray to prevent rupture from excess heat.

Unusual Fire and Explosion Hazards – None Known

Hazardous Products: Thermal decomposition of this product may generate oxides of carbon.

SECTION V

Reactivity Data

Stability: Stable
Hazardous Polymerization: Will not occur
Incompatibility: Do not mix with other chemicals.
Conditions to Avoid – None Known

N/A = Not Applicable, N/E = Not Established, N/D = No Data, N/R = Not Required

SECTION VI

Health Hazard Data

Primary Route of Entry: Skin or eye contact, inhalation.

Eye Contact: Direct contact may cause eye irritation.

Skin Contact: Prolonged contact may cause transient reddening of the skin.

Inhalation: Trace components vapors may be irritating to eyes, mucous membrane, respiratory tract and produce headache or nausea.

Ingestion: If swallowed, this product may cause irritation of mucosal linings of the mouth, throat, esophagus or stomach. May cause diarrhea.

Chronic Overexposure: None.

SECTION VII

First Aid

Eyes: Flush eyes with water until water is no longer cloudy.

Skin: Wash skin with soap and water. If clothes are soaked, remove and wash before reuse.

Ingestion: If ingested: Do not induce vomiting. Drink several glasses of water and get immediate medical attention.

Inhalation: No emergency care anticipated.

Note to Physician: There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition.

SECTION VIII

Special Protection Information

Respiratory Protection: None should be required. Use NIOSA approved respirator in poorly ventilated areas.

Ventilation: General mechanical room ventilation is adequate.

Eye Protection: Use safety glasses.

Skin Protection: Gloves impervious to soap and water.

SECTION IX

Spill or Leak Procedures

Steps to be taken if material is released or spilled: Restrict area to only those personnel needed. Major spills should be collected for disposal. Minor spills may be flushed to sewer if permitted by state, federal and local regulations.

Waste Disposal Method: Incinerate or bury in suitable landfill.

SECTION X

Shipping Data

D.O.T. Shipping Name: Paint Related Material

D.O.T. Hazard Class: Not Regulated

UN/NA Number: N/A

Reportable Quantity: None

D.O.T. Labels Required: None

NMFC # 149980-2

Freight Class: 55